

SYNTH CSX OG-00 HD (Synergetic heavy duty & Calcium Sulfonate-Complex)

(Latest generation synthetic high temperature heavy duty Calcium sulfonate complex / Polymer grease with special white solid lubricants for optimum protection of your gear drive for increased life span and cost reduction)

DESCRIPTION:

SYNTH CSX OG-00 HD is a premium heavy duty & high temperature synergetic grease for very high powered medium to large size with low speed gear drive to large girth gear drives tooth flanks, rotary mills & kilns. It is formulated with extreme pressure, anti-wear additives package and high film strength cylinder synergetic (semi-synthetic) base oil with powerful balanced blend of calcium sulphonate complex with special white solid lubricants in a heavy duty application provides thicker and stronger film stability. **SYNTH CSX OG-00 HD** gives high protection by minimizing metal-to-metal contact and reduces friction, wear at minimal consumption. It contains small dosage of special synthetic polymers, synthetic (PAO) ester additives with special white solid lubricants Mox-Active (Organo Molybdenum Complex) a German technology improvement additive creates a passive film on friction surfaces before friction occurs, optimum wear protection, vibrations & heavy shock loads in gear tooth flanks. All of this turn reduces maintenance cost and extend the life of equipment and friction elements avoiding seizure & expensive repairs. This product has been developed to withstand extremely heavy load, slow moving, large open gear drives operating in very hostile environments. High solid content and calcium sulfonate complex thickener it will not slide down the shank of the tool during its operation.

APPLICATIONS

- **SYNTH CSX OG-00 HD** has been designed to lubricate: Grinding Mills, Kilns, Shovels, Draglines, Calciners, Journal, Roller & Sleeve bearings, Transmission brasses, gear tooth flanks, Crown wheels, Transmissions open gears & Crystallizer transmission gears & Rotating dryer gears.
- **Application Industry:** Sugar, Steel, Paper, Mining, Cement, Chemical, Marine & Offshore.
- **SYNTH CSX OG-00 HD** can be applied by high pressure spray systems, immersion, transfer paddle wheel, pressure fed circulation and total loss spray lubrication systems. It is suggested for heavy duty gear drives working at low speeds.

FEATURES /BENEFITS

- Good water, heat resistance and are not affected by mild acids / alkalis.
- Good corrosion protection and oxidation stability with high drop point.
- Excellent flow and pump-ability for automatic centralized and Individualized systems.
- Thermally stable, can withstand high shock loads, and minimizing metal to metal contact.
- High drop point ensures extended operating temperature range upto -20°C to 180°C.
- Good low temperature pump ability, Good wear protection and Long lasting lubrication.
- You can work with your breaker for long, continuous periods, even in warmer climates.
- Low consumption, Immediate monetary savings, extends bearings life and gives longer relubrication intervals. High protection against seizure and wear, avoiding expensive repairs.

PROPERTIES

SPECIFICATIONS	SYNTH CSX OG-00 HD
NLGI Grade available	00
Colour & Appearance	Brownish, Sticky & Tacky
Base Oil	Semi-Synthetic
Thickener Soap	Calcium Sulphonate Complex
Solid Lubricants	Mox-Active (Organo Molybdenum Complex) + PAO Ester + Polymer
Viscosity @ 40°C, Cst	5000-6000
Work Penetration	400-430
Drop Point	+280
Service Temperature	-20°C to 180°C
Weld Load	+800

POWERMAXX LUBE INDIA

Website: www.powermaxxlube.com Email: info.powermaxx918@gmail.com, info@powermaxxlube.com

Contact Number: 996748763, 7506973307